

## DUAL USE Pulse Dampers, for Flow Smoothing AND Pressure Pulsation Interception, by multi-connection THRU-FLOW



Bitte Fon Alfred Hasche Fax --49(0)211-23 10 19  
Fon --49(0)211-23 60 40 flowmatic.gmbh@t-online.de

### *The Pipelugger /LP range, by PulseGuard*

**D23a**

Large diameter, liquid chamber, relative ports, dissipates pressure waves, Large diameter bladder response even at .05 Bar.  
Corrosive Liquids go inside bladders, SAVING COST OF TITANIUM, HASTELLOY, TANTALUM, etc. VESSEL SHELLS.  
When only one connection required and no in place flushing, save a "T" for RV, Drain, or Gauge, and use damper second connection.

Drawing number will include

#### Inventory

from columns below.

#### Specification

#### Service

Part Number Replace ** with ss A20, HastC276 etc.	In3	Ba	Connections (to pump / to sys.)	Std CL to CL	Single flange face, Max within damper damper diameter.	Metric equivalent to ANSI B 16.5	Std Vol (Lit)	Design pres. In 316L ss @93C or 200F <NB>	Length without pipes (inches / mm)	Diameter (inches / mm)	Wt (Kg)	Spares Kit please add Elastomer designation for the "?"
PeG-**-	10i	10	1/8"x1/8" NF		3/4" 600#		0.16	1450p	5.2 / 130	3.0 / 76	2.2	D64y42 ?
PeG-SS-	20i	10	3/8"x3/8" NF		1/2" 150# /	DN10PN100	0.33	1450p	5.2 / 130	4 / 101	4.5	D85L ?
PeG-SS-	40i	10	1/2"x3/8" NF		1/2" 300#	/DN25PN40	0.66	1450p	6.7 / 170	5.5 / 139	9	D115L ?
PeG-SS-	61i	50	3/4"x1/2" NF		1.0" 600# /	DN25PN40	1	750p	6.9 / 175	6.0 / 152	8.2	D125y65 ?
PeG-SS-	92i	40	1.0"x3/4" NF		1.5" 300# /	DN40PN40	1.5	600p	6.9 / 175	6.5 / 165	11	D145y75 ?
PeG-SS-	183i	40	1.0"x1.0" NF		2.5" 300# /	DN65PN40	3	600p	8.5 / 213	8.5 / 216	17	D191y65 ?
PeG-SS-	366i	30	1.5"Mx1.0" NF		4.0" 300# /	DN125PN16	6	425p	9.4 / 239	10.4 / 264	25	D244L ?
PeG-SS-	733i	25	2"NMx2" NM		5.0" 150# /	DN150PN16	12	365p	10.1 / 256	12.7 / 322	37	ND285y128 ?
PeG-SS-	1000i	25	3"NMx2" NM		6.0" 150# /	DN200PN10	18	365p	11.8 / 300	14 / 356	52	ND328y123 ?
PeG-SS-	1650i	25	4"Wx4"W 45x45		8.0" 150# /	DN200PN25	27	365p	16 / 406	16 / 606	74	ND368y178 ?
PeG-SS-	2200i	25	5"Wx5"W 45x45		10" 150# /	DN250PN25	36	365p	22 / 560	20 / 508	100	ND450y120 ?