

## Medium, High, Super, &amp; Ultra Pressure "GAS BAG" Stainless Pulse Dampers

***The Dual Use PipeGuard/HP range by PulseGuard***

The original 1965, no poppet to jam, no glue or bonds, with internal web stabilisation.

Twin connections are off the shelf inventory items, if you do not wish to have in place flush before service, or constant temperature and no pressure pulsation interception, then save the cost of an extra "T", and use the 2nd connection for RV, Drain, or Gauge.

Inventory			The drawing number will include model number plus the numbers below				Price	Specification			Service
Ordering (Insert material preferred ** into model number)	In3	Bar	Connections max for this volume to pump - to sys - connection type	Bolt hole face mates with "O" ring in piping block SF-"O". BS4504 DIN 2501 / ANSI B 16.5	Standard Volumes (Liters)	Pres. @ 93 C Std. PSI (N.B.)	\$s or E FOB NC USA or Stockport UK in 316L ss	Length without pipes (inch/mm)	Diameter (inch/mm)	Weight (Kg)	Spares Kit Pt. Nbr.
PiG-**	6.0i	207	3/8"Fx1/4"FN	1/2" 250#	0.1	3000p		7.125 / 181	2.5 / 63	6	B44x75 ?
PiG-SS	15i	240	1/2"Fx3/8"FN	4x3/8" on 2.25" PCD	0.25	3500p		8.54 / 217	2.8 / 70	10	B57x98 ?
PiG-SS	40i	140	3/4"Fx1/2"FN	4x1/2" on 2.5" PCD	0.65	2000p		11.1 / 282	3.5 / 89	15	B62x207 ?
PiG-SS	75i	140	1.0"Fx3/4"FN	4x1/2" on 2.5" PCD	1.25	2000p		17.0 / 432	3.46 / 88	22	B72x315 ?
PiG-SS	100i	145	1.25"Mx1.0"FN	4x3/4" on 3.5" PCD	1.5	2100p		13.76 / 350	4.49 / 114	25	B98x232 ?
PiG-SS	120i	145	1.5"Mx1.5"MN	4x3/4" on 3.5" PCD	2	2100p		15.94 / 405	4.49 / 114	27	B98x300 ?
PiG-SS	170i	131	2.0"Mx1.5"MN	DN20PN258 / 1" 1500#	2.8	1900p		14.37 / 365	5.55 / 141	36	B123x250
PiG-SS	200i	131	2.0"Mx2.0"MN	DNMPN291 / 1" 1500#	3.28	1900p		16.46 / 423	5.55 / 141	40	B123x295
PiG-SS	250i	131	2.0"Mx2.0"MN	DNMPN291 / 1" 1500#	4	1900p		18.5 / 470	5.55 / 141	45	B123x357
PiG-SS	120i	240	3.0"Mx2.0"MW	DN25PN410 / 1" 2500#	2	3500p		11.8 / 300	6.7 / 170	30	B139x105
PiG-SS	240i	240	3.0"Mx2.0"MW	DN25PN410 / 1" 2500#	3.9	3500p		15.7 / 400	6.7 / 170	37	B139x205
PiG-SS	488i	240	3.0"Mx2.0"MW	DN25PN410 / 1" 2500#	8	3500p		24 / 610	6.7 / 170	46	B139x420

These sizes, also available at 1500PSI / 100Bar ARE NOT ALWAYS "OFF THE SHELF INVENTORY"

26b

PiG-SS	693i	207	3"Mx3"MW	DN65PN250 / 2" 1500#	11.4	3000p		24 / 610	8.62 / 219	96	B195x360
PiG-SS	1220i	241	3"Mx3"MW	DN80PN250 / 2.5" 2500#	20	3500p		30 / 760	10.75 / 273	177	B230x500
PiG-SS	2135i	241	4"Mx4"MW	DN100PN160 / 3" 2500#	35	3500p		36 / 915	12.75 / 324	290	B260x600
PiG-SS	3050i	172	5"Mx5"MW	DN150PN250 / 4"1500#	50	2500p		42 / 1067	14 / 356	340	B300x700
PiG-SS	1.0i	414	1/4"x1/4"FN	Not Applicable	0.016	6000p		4.6 / 117	1.77 / 45	3	B24x50 ?
PiG-SS	2.0i	414	1/4"x1/4"FN	Not Applicable	0.032	6000p		6 / 152	1.77 / 45	4	B24x80 ?
PiG-DSS	6.0i	1034	3/8"x1/4"M AE	4x1/2" on 2.5" PCD	0.1	15000p		7.5 / 190	3.5 / 89	17	B44x75 ?
PiG-DSS	15i	776	1/2"x3/8"M AE	4x5/8" on 2.75" PCD	0.25	11250p		10.0 / 254	4.0 / 102	26	B57x98 ?
PiG-SDSS	60i	759	1.0"x3/4"M AE or H	1/2"2500#	1	11000p		16.0 / 406	5.1 / 130	70	B72x255 ?