

D22a *PumpGuard /RF Range, by PulseGuard*

PULSE DAMPER WITH ELASTOMER FLEX-TUBE, EP, NITRILE, FLUORO etc.

For sludge, slurry, particulate, and high viscosity liquids.

Please call your local distributor for current materials surcharges and quantity quantity discounts, or 1-888-326-7377

PumpGuard /RF in standard 316 SS wetted with carbon steel external trim

Spares Kit

Dimensions, Weights, Nominal Volume, and Prices, 275psi series - 16 bar series

State with or without PermaCushion foam or support tube

Model Number / Material	ANSI B16.5 Flng Face 150#	DN -- PN 16 -	Volume	Raised face to Raised face	Outside Diameter	Estimat Seal Weight	Seal Bead OD	Neck OD	Lump OD	Tube Ctr OD	Tube Length
Pug 0.7 RF	3/4"	12	0.7 gal / 2.6 ltr	32 in / 812 mm	4 in / 101 mm	17 kg	41 mm	26 mm	89 mm	60 mm	679 mm
Pug 1.4 RF	1.0"	20	1.4 gal / 5.3 ltr	32 in / 812 mm	4.5 in / 114 mm	19 kg	41 mm	26 mm	99 mm	70 mm	679 mm
Pug 2.1 RF	1.25"	25/32	2.1 gal / 8.0 ltr	32 in / 812 mm	5.56 in / 141 mm	29 kg	52 mm	38 mm	122 mm	90 mm	680 mm
Pug 3.0 RF	1.5"	40	3 gal / 11.5 ltr	32 in / 812 mm	6.62 in / 168 mm	43 kg	52 mm	38 mm	154mm	116 mm	680 mm
Pug 4.5 RF	2.0"	50	4.5 gal / 17 ltr	46 in / 1168 mm	6.62 in / 168 mm	56 kg	74 mm	58 mm	154 mm	116 mm	1013 mm
Pug 8.0 RF	2.5"	65	8 gal / 30 ltr	46 in / 1168 mm	8.62 in / 219 mm	84kg	120 mm	100 mm	203 mm	148 mm	1223 mm
Pug 10 RF	3.0"	80	10 gal / 38 ltr	55 in / 1400 mm	8.62 in / 219 mm	102 kg	120 mm	100 mm	215 mm	185 mm	1223 mm
Pug 15 RF	4.0"	100	15 gal / 57 ltr	55 in / 1400 mm	10.7 in / 272 mm	177kg	164 mm	140 mm	288 mm	225 mm	1452 mm
Pug 19 RF	5.0"	125	19 gal / 72 ltr	64 in / 1626 mm	10.7 in / 272 mm	214 kg	164 mm	140 mm	309 mm	225 mm	1452 mm
Pug 26 RF	6.0"	150	26 gal / 100 ltr	64 in / 1626 mm	12.7 in / 322 mm	264 kg	239 mm	216 mm	325 mm	270 mm	1456 mm
Pug 30 RF	8.0"		30 gal / 115 ltr	66 in / 1676 mm	16 in / 406 mm	477 kg	274 mm	249 mm	450 mm	360 mm	1456 mm
Pug 42 RF	10.0"		42 gal / 160 ltr	66 in / 1676 mm	20 in / 508 mm	555 kg	274 mm	249 mm	450 mm	360 mm	1456 mm
Pug 60 RF	12.0"		60 gal / 230 ltr	80 in / 2033 mm	22 in / 559 mm	905 kg	342 mm	318 mm	500 mm	390 mm	1810 mm