

Dampers, For Pressure Pulsation Interception, by multi connection THRU-FLOW

## ***The WaveGuard /RJ Range by PulseGuard***

PULSE DAMPER PRICES WITH RAM JET TECHNOLOGY. Requires some Delta P.

Only for use on clean liquids, at frequencies above 10 Hz.

Please call your local distributor for current materials surcharges and quantity discounts, or 1-888-326-7377

Wag / RJ / --e / --P / --	Nominal Volume		Working Pres. -- P		Vessel Diam.		Raduis R		Weight Est.		Connection	Price 180 degrees or 90 degrees
	"e" Nbr.	Gls.	Ltrs.	P=psi	B=Bar	ins.	mm	ins.	mm	lbs.	Kg	Inch Pipe
<b>316 STAINLESS STEEL Dual Certified</b>										<b>Without Flanges</b>	<b>Butt Weld 37 degrees Std.</b>	<b>List 1 Pc.</b>
0.6	0.25	0.95	4700	320	5.56	141	5.5	140	24	11	1/8"	
1.2	0.5	1.9	4600	315	6.62	168	6.25	159	39	18	1/4"	
2.4	1.1	4	3700	252	8.62	219	7.75	197	62	28	3/8"	
5	3.2	12	3700	252	12.7	323	10.25	260	208	95	1/2"	
9	6	22	3450	235	14	356	11	279	270	123	3/4"	
14	9	33	3400	252	16	406	14	355	365	166	1.0"	
25	13	50	3350	230	18	457	16	406	530	240	1.5"	
30	18	68	3350	230	20	508	18	457	760	345	2.0"	
50	31	119	3650	250	24	609	20	508	1410	640	2.5"	
99	43	165	3220	222	30	756	21	533	1110	505	4.0"	
132	58	220	3280	226	33	834	22	558	1500	683	6.0"	
149	66	250	3240	224	34	868	23	584	1680	764	8.0"	
205	89	340	3320	229	38	966	26	660	2340	1063	10"	
576	250	950	3130	216	54	1352	39	990	6030	2742	12"	